



Flexible Lance Extension

Model **36290**

FEATURES

- Durable stainless steel linked, outer cover with single wire braid interior hose for durability.
- Cleaning flexibility with full 90 degree bend.
- Compatible with hot or cold fluids.
- Lightweight, easy installation onto lance end.

SPECIFICATIONS

	U.S. Measure	Metric Measure
Maximum Flow.....	10 GPM	(38 L/M)
Maximum Pressure	3000 PSI	(210 BAR)
Maximum Temperature.....	190°F	(88°C)
Inlet Fitting	1/4" NPT	(1/4" NPT)
Nozzle Fitting	1/4" NPT	(1/4" NPT)
Weight	16 oz.	(0.45 kg)
Overall Length.....	13"	(330 mm)

“Customer confidence is our greatest asset”

SELECTION: Attached to any 1/4" 3000 PSI rated lance.

INSTALLATION: Remove the spray nozzle from the standard lance and thread the nozzle into the nozzle holder on the flexible lance extension. Place teflon tape or sealant on male end of flexible extension and attach to standard lance.

MAINTENANCE: Discontinue use and replace flexible lance extension if leaks occur from the outer stainless steel linked hose cover.

WARNING

Always shut system off when changing guns, lances and nozzles.

CAUTION

This flexible lance extension is not intended to be used with steam.

WARNING

Severe injury can occur with high pressure spray. Do not allow spray to contact any part of body.

WARRANTY

90 Day Warranty

Refer to complete Cat Pump Warranty for further information.

Products described hereon are covered by one or more of the following U.S. patents 3558244, 3652188, 3809508, 3920356, 3930756 and 5035580

Feb 1998 2898

World Headquarters

CAT PUMPS

1681 - 94th Lane N.E. Minneapolis, MN 55449-4324

Phone (612) 780-5440 — FAX (612) 780-2958

e-mail: sales@catpumps.com

www.catpumps.com

International Inquiries

FAX (612) 785-4443

e-mail: intlsales@catpumps.com



CAT PUMPS (U.K.) LTD.

1 Fleet Business Park, Sandy Lane, Church Crookham, Fleet

Hampshire GU13 0BF, England

Phone Fleet 44 1252-622031 — Fax 44 1252-626655

N.V. CAT PUMPS INTERNATIONAL S.A.

Heiveldkens 6A, 2550 Kontich, Belgium

Phone 32-3-450.71.50 — Fax 32-3-450.71.51

e-mail: cpi@catpumps.be

CAT PUMPS DEUTSCHLAND GmbH

Buchwiese 2, D-65510 Idstein, Germany

Phone 49 6126-93030 — Fax 49 6126-930333

e-mail: catpumps@t-online.de