

SPECIFICATIONS

AIR:

**20 AMP SERVICE REQUIRED
110 VOLT, 14 AMPS
60 HZ
1.5 HORSEPOWER
ONE CYLINDER
ONE STAGE
OIL-LESS**

SCFM @ PSI:

**6 @ 0
5 @ 20
4.1 @ 40
3.1 @ 90
2.9 @ 100
2.1 @ 125 (MAX PSI)**

**TEMPERATURE RANGE: -10
DEGREES F TO 100
DEGREES F.**

MOTOR:

**1.5 HP, 1725 RPM
CAPACITOR START,
NEMA 56 FRAME,
AUTOMATIC THERMAL
OVERLOAD.**

**NO LUBRICATION REQUIRED ON
MOTOR OR COMPRESSOR.**

AIR:

**20 AMP SERVICE REQUIRED
220 VOLT, 7 AMPS
60 HZ
1.5 HORSEPOWER
ONE CYLINDER
ONE STAGE
OIL-LESS**

SCFM @ PSI:

**6 @ 0
5 @ 20
4.1 @ 40
3.1 @ 90
2.9 @ 100
2.1 @ 125 (MAX PSI)**

**TEMPERATURE RANGE: -10
DEGREES F TO 100
DEGREES F.**

MOTOR:

**1.5 HP, 1725 RPM
CAPACITOR START,
NEMA 56 FRAME,
AUTOMATIC THERMAL
OVERLOAD.**

**NO LUBRICATION REQUIRED ON
MOTOR OR COMPRESSOR.**

